

REMARKS

The above amendment is believed to place the claims in proper condition for examination.  
Early and favorable action is awaited.

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached page is captioned "Version with markings to show changes made."

In the event there are any additional fees required, please charge our Deposit Account No.  
01-2340.

Respectfully submitted,

ARMSTRONG, WESTERMAN, HATTORI,  
McLELAND & NAUGHTON, LLP

*William L. Brooks* Reg. No. 22,631  
for, William L. Brooks  
Reg. No. 34,129

Atty. Docket No. 010811  
Suite 1000  
1725 K Street, N.W.  
Washington, D.C. 20006  
Tel: (202) 659-2930  
WLB/yap

09857207 101601

Mikio TOTANI

Docket No. 010811

VERSION WITH MARKINGS TO SHOW CHANGES MADE

Claims 6-8, 11-13 and 16-18 have been amended as follows:

6. (Amended) The apparatus as set forth in any one of claims 1 to [5] 3 wherein said plastic film means is fed longitudinally thereof and intermittently, said plastic film means being heat sealed widthwise thereof whenever intermittently fed, said optical sensor then detecting the heat sealed place of plastic film means whenever said plastic film means is intermittently fed, a cutter being disposed at a position and moved by position adjustment means to adjust the position of edge of cutter in a direction parallel to the direction in which said plastic film means is fed, in response to a detecting signal transmitted from said optical sensor so that said plastic film means can be cut along a line predetermined at or near the heat sealed portion thereof by said cutter.

7. (Amended) The apparatus set forth in any one of claims 1 to [5] 3 wherein said plastic film means is fed longitudinally thereof and intermittently for a length, said plastic film means being heat sealed widthwise thereof by seal bar means disposed at a position whenever said plastic film means is intermittently fed, said optical sensor then detecting the heat sealed place of plastic film means whenever said plastic film means is intermittently fed, to adjust the feed length of plastic film means or the position of heat seal bar means in response to a detecting signal transmitted from said optical sensor so that said plastic film means can be cut along a line predetermined at or near the heat sealed portion thereof by a cutter.

8. (Amended) The apparatus as set forth in any one of claims 1 to [5] 3 wherein standing pouches are made from said plastic film means, each of the slanding pouches comprising rectangular panel materials which are superposed into two layers to have bottom and opposite sides edges, a bottom material being folded into halves, superposed into two layers and interposed between the layers of panel material at the bottom edges thereof, one of said layers of panel material being bottom

sealed with one of said layers of bottom material to include a bottom sealed portion formed along the bottom edge of panel material, the other layer of panel material being bottom sealed with the other layer of bottom material to include a bottom sealed portion formed along the bottom edge of panel material, said layers of panel material being cross sealed with each other to include cross sealed portions formed along the opposite side edges of panel material, each of the bottom and cross sealed portions having the minutely rugged surface, said optical sensor reading out the minutely rugged surfaces of bottom and cross sealed portions to judge whether the relation in place between the bottom and cross sealed portions is good or no good, whenever said panel and bottom materials are fed widthwise of the standing pouches and intermittently after being bottom and cross sealed in a standing pouch making process.

11. (Amended) The apparatus as set forth in [any one of claims 8 to 10] claim 8 wherein punch holes are formed in said bottom material at intersections between the bottom and cross sealed portions, said layers of panel material being partially sealed with each other at the places of punch holes, said punch holes protruding from the cross sealed portions to have protruding portions formed on the opposite sides of the cross sealed portions, each of the protruding portions having a surface which is not or barely minutely rugged, said optical sensor judging whether the relation in place between the punch holes and the bottom and cross sealed portions is good or no good, in accordance with the place of protruding portion.

12. (Amended) The apparatus as set forth in [any one of claims 8 to 11] claim 8 wherein said cross sealed portions have center lines along which notches are formed into the cross sealed portions from the bottom edges of panel material, said optical sensor judging whether the relation in place between the notches and the bottom and cross sealed portions is good or no good.

13. (Amended) the apparatus as set forth in any one of claims 1 to [5] 3 wherein standing pouches are made from said plastic film means, each of the standing pouches comprising rectangular panel materials which are superposed into two layers to have bottom and opposite side edges, a bottom material being folded into halves, superposed into two layers and interposed between the layers of panel material at the bottom edges thereof, one of said layers of panel material being bottom sealed with one of said layers of bottom material to include a bottom sealed portion formed along the bottom edge of panel material, the other layer of panel material being bottom sealed with the other layer of bottom material to include a bottom sealed portion formed along the bottom edge of panel material, said layers of panel material being cross sealed with each other to include cross sealed portions formed along the opposite side edges of panel material, each of the bottom and cross sealed portions having the minutely rugged surface, said optical sensor reading out the minutely rugged surfaces of bottom and cross sealed portions to judge whether the relation in place between the bottom and cross sealed portions is good or no good, when said standing pouches are fed widthwise thereof after being made.

16. (Amended) The apparatus as set forth in [any one of claims 13 to 15] claim 13 wherein punch holes are formed in said bottom material at intersections between the bottom and cross sealed portions, said layers of panel material being partially sealed with each other at the places of punch holes, said punch holes protruding from the cross sealed portions to have protruding portions formed on the opposite sides of the cross sealed portions, each of the protruding portions having surface which is not or barely minutely rugged, said optical sensor judging whether the relation in place between the punch holes and the bottom and cross sealed portions is good or no good, in accordance with the place at protruding portion.

17. (Amended) The apparatus as set forth in [any one of claims 13 to 16] claim 13 wherein each of said standing pouches are corner cut at corners between the bottom and opposite side edges

thereof to give an appearance, said optical sensor judging whether the appearance of corner cutting is good or no good.

18. (Amended) The apparatus as set forth in any one of claims 1 to [5] 3 wherein standing pouches are made from said plastic film means, each of standing pouches comprising rectangular panel materials which are superposed into two layers to have bottom and opposite side edges, a bottom material being folded into halves, superposed into two layers and interposed between the layers of panel material at the bottom edges thereof, one of said layers of panel material being bottom sealed with one of said layers of bottom material to include a bottom sealed portion formed along the bottom edge of panel material, the other layer of panel material being bottom sealed with the other layer of bottom material to include a bottom sealed portion formed along the bottom edge of panel material, said layers of panel material being cross sealed with each other to include cross sealed portions formed along the opposite side edges of panel material, each of the bottom and cross sealed portions having the minutely rugged surface, said optical sensor reading out the minutely rugged surfaces of cross sealed portions to judge whether the sealed width of cross sealed portion is good or no good, when said standing pouches are fed widthwise thereof after being made.